

Original post set 1820 by Hendricks with witnesses: 10" ash S 42 W 7 links; 48" elm N 43 E 14 links per Marion County Atlas pg. 14. John Coyner 12-26-1894 indicates no stone but the following witnesses: 30" oak N 16 1/2 E 95 1/2 feet; 22" oak N 76 E 67' per Warren Township Legal Survey Book pg. 58. Baden 8-5-55 called a road nail with brass washer. Hankins 6-23-58 called road nail w/brass washer. McLand 1-30-69 called railroad spike, Hylden 6-13-74 called a bolt. Wilcoxen 4-1-76 called a bolt. Gries 10-27-87 called railroad spike set. Kiste 10-21-94 called railroad spike with a punch hole. 7-21-99 Wilcoxen excavated and railroad spike w/punch hole was found 2" down. A bolt spike found 6" down. A frost pin found 0.2' E & 0.34' N of bolt spike. Railroad spike found 14" down. Stone found 18" down. Harrison set. Re-tied 07-21-99 by Wilcoxen.

REF.	DISTANCE	DESCRIPTION
,	50.31	PK nail S PwP#8-581 A 12"up
2.	134.95'	PK nail W PwP#22-581 14"up
3.	27.46	Mag nail w/brass washer NE PwP#23-581 12"up
4.	85.53'	Top nut of fire hydrant
ō.	188.96	PK nail W PwP#24-581 14"up